




Customer Ref: \_\_\_\_\_

Hose Kit


Quantity: \_\_\_\_\_

**1. OPTIONAL IN-LINE EQUIPMENT TO REPLACE THE Y-BALL VALVE**


Venturi Mesurmeter Balance Valve w/ PT & Memory Stop



Auto. Mesurflo w/PT's & B/V



Deluxe Ball Valve w/ PT & Memory Stop



**Automatic Temperature Control Valve Type**


Customer Supplied  
Field Supplied/Installed

SIZE: \_\_\_\_\_

**Hays Supplied Options:**

- 24V, floating 3-wire, 2 position zone valve
- 24V, 0-10 vdc proportional, 3-wire zone valve PO/PC
- 24V, 2-wire, spring return normally open
- 24V, 2-wire, spring return normally closed
- 120V, 2-wire, spring return normally open
- 120V, 2-wire, spring return normally closed

**1. Automatic Balancing Valve w/ PT's**



**2.**

**Building PPG Connection Type**

- Male NPT      Size: \_\_\_\_\_
- Female SWT
- Female NPT
- International Size

**3. Flow Rate: \_\_\_\_\_ GPM**

**5.**


**Hose Diameter      Length**

1/2"	12"
3/4"	18"
1"	24"
1-1/4"	36"
1-1/2"	48"
Custom Size: _____	

**Coil PPG Connection Type**

- Male NPT      Size: \_\_\_\_\_
- Female SWT
- Female NPT
- International Size

COIL



**7. Ball Valve w/ PT**

**Additional notes:**

\_\_\_\_\_

**Tagging Info:**

\_\_\_\_\_

**7. Optional Equipment:**

**Y-ball Strainer w/PT & BDVHC** (Replaces Ball Valve) →

**Lever Handles** Optional on smaller sizes/Standard on 1 1/4 size & up.

**Manual Air Vent** Optional on Return Coil Connection

**Ext. Kit A.** Optional Extended Handles and Extended PT's

**Ext. Kit B.** Optional Extended Handles, Extended PT's and Manual AV Ext.

**Stainless Steel Tag Kit**

- IMPORTANT: HAYS FLUID CONTROLS CANNOT GUARANTEE THAT ALL HOSE KITS WILL FIT WITHIN THE CONFINES OF A SPECIFIC INSTALLATION AREA.
- ALL HAYS HOSE KITS ARE ASSEMBLED AND LEAK TESTED